

# Nano2.5G Ethernet Transformers

Single Port 2.5GBASE-T Small Form Factor Isolation Modules



## Product Features:


- 2.5GBASE-T Miniature Package
- IEEE802.3bz/af/at/bt<sup>1</sup>
- 4PPoE - 4 Pair Power over Ethernet
- Robust Patented Open Frame Construction
- 1500Vrms Hi-Pot
- UL/EN60950 recognized
- 100% Compliance Testing

US Patent Numbers:  
 5,656,985 6,297,721 B1  
 6,297,720 B1 6,320,489 B1  
 6,344,785 B1 6,662,431 B1

Part Number	Data Rate	Total Power <sup>2</sup>	Current Per Pair	Temp. Range	Turns Ratio
TG2G-S13NYNLF	2.5G	30W	350mA	0 to +70°C	1CT:1CT
TG2G-E13NYNLF	2.5G	30W	350mA	-40 to +85°C	1CT:1CT
TG2G-HPE3NYNLF	2.5G	60W	600mA	-40 to +85°C	1CT:1CT


Notes:  
<sup>1</sup> The IEEE802.3bt standard has not been officially ratified.  
<sup>2</sup> Power rating reduced to half when using only two pairs for power as in 802.3af/802.3at applications.  
 Please contact the factory or representative for individual datasheets or additional information.

## Package



Recommended Solder Pad

## Circuit B



\*Pins 13-24 located on line side

Dimensions: inch [mm]  
 Co-Planarity: 0.004 [0.10]



2880 Lakeside Drive #116  
 Santa Clara, CA 95054  
 (650) 903-3800  
[www.haloelectronics.com](http://www.haloelectronics.com)

HALO® Electronics is a leading supplier of high quality communication magnetics including signal transformers, filters, CMR chokes, PoE power transformers, DC/DC converters, and integrated Ethernet connectors. HALO's high quality leading edge technology solutions are manufactured in ISO9001 and ISO14001 factories.